


**Model 354**

**Application**

- Double acting.
- Non-handed.
- Maximum weight: 75lbs.
- Dwarf doors from 2'2" to 3'0" wide.

**Product Description and Features**

- Surface mounted top pivot: 3541020.
- Recommended for office rail gates, partitions, and lavatory stall doors.
- 1-3/4" door thickness.
- Maximum opening 90°.
- Arm adjustment. Door normally comes to rest at closed position. If door is to remain open, arm is set on spindle so door comes to rest at 90°.
- Package also includes closer bracket and flange style arm.
- Carry full weight of door when pivotal hung.
- Quiet control; no slamming or flapping.
- All moving parts enclosed and fully immersed in lubrication checking fluid.
- Finishes available: 689, 690, 691 and 695.



*Model 354  
With Surface  
mounted top pivot.*


**Model 355**

**Application**

- Double acting.
- Non-handed.

**Product Description and Features**

- Surface mounted top pivot: 3551020.
- Recommended for office rail gates, partitions, and lavatory stall doors.
- 1-3/4" door thickness.
- Maximum opening 90°.
- Arm adjustment. Door normally comes to rest at closed position. If door is to remain open, arm is set on spindle so door comes to rest at 90°.
- Package also includes closer bracket and flange style arm.
- Carry full weight of door when pivotal hung.
- Quiet control; no slamming or flapping.
- All moving parts enclosed and fully immersed in lubrication checking fluid.
- Finishes available: 689, 690, 691 and 695.



*Model 355  
With mortise  
top pivot.*


**Model 356**

**Application**

- Double acting.
- Non-handed.
- Maximum weight: 75lbs.
- Dwarf doors from 2'2" to 3'0" wide.

**Product Description and Features**

- Surface mounted top pivot: 3541020.
- Recommended for office rail gates, partitions, and lavatory stall doors.
- 1-3/4" door thickness.
- Maximum opening 90°.
- Arm can be adjusted so that door stands ajar at any degree.
- Package also includes closer bracket and arm that may be surface mounted or mortised.
- Carry full weight of door when pivotal hung.
- Quiet control; no slamming or flapping.
- All moving parts enclosed and fully immersed in lubrication checking fluid.
- Finishes available: 689, 690, 691 and 695.



*Model 356  
With Surface  
mounted top pivot.*

**Gate Closers**

**Model 357**

**Application**

- Double acting.
- Non-handed.

**Product Description and Features**

- Surface mounted top pivot: 3551020.
- Recommended for office rail gates, partitions, and lavatory stall doors.
- 1-3/4" door thickness.
- Maximum opening 90°.
- Arm can be adjusted so that door stands ajar at any degree.
- Package also includes closer bracket and arm that may be surface mounted or mortised.
- Carry full weight of door when pivotal hung.
- Quiet control; no slamming or flapping.
- All moving parts enclosed and fully immersed in lubrication checking fluid.
- Finishes available: 689, 690, 691 and 695.



*Model 357  
With mortise  
top pivot.*



**Model 359**

**Application**

- Single acting.
- Non-handed.
- Maximum weight: 75lbs.
- Dwarf doors from 2'2" to 3'0" wide.

**Product Description and Features**

- Recommended for office rail gates, partitions, and lavatory stall doors.
- 1-3/4" door thickness.
- Maximum opening 140°.
- Surface mounted to edge of partition with edge wide enough for 1-1/2" bracket.
- Door hanging means by others.
- Track style arm.
- Package includes closer, bracket, and slide track arm.



*Model 359*